

## Prevent costly radioactive contamination of your scrap yard, steel plant, equipment, product and personnel with the RC2000 series vehicle radiation detection system!

- Innovative Design with Multiple Detector Sizes
- User Friendly, Easy to Operate
- Detailed Data Storage
- Adjustable Alarm Threshold Settings
- Network Capability with Email
- Easy to install and setup.

# RC2000

## VEHICLE RADIATION DETECTION SYSTEMS

### Detection of Radioactivity in Moderate Density Materials

The RC2000 series of radiation detection systems have been designed for moderate density materials such as compressed waste and processed scrap metal. The vehicle size and type will help determine the appropriate detector panel size (69L, 91L, 138L) and configuration. The RC2000 detection systems all utilize RadComm's high quality specially prepared Polyvinyl Toluene (PVT) scintillators, electronics and Photomultiplier Tube (PMT).

### Simplified System Operation

The RC2000 provides a high level of detection capability for buried Gamma Ray sources in low to moderate material densities. System operation is completely automated providing specific alarm thresholds in real-time during each scanning period. The RC2000 series utilize a User Friendly Graphical interface allowing the operator to easily move through the wide range of User options. Detailed alarms records are stored on the internal hard drive and can be easily retrieved.

### Networkable Remote System Access

The RC2000 Controller is equipped with a network adaptor allowing remote monitoring, data retrieval and maintenance functions. The internal RC2000 software and hardware designs are extremely flexible allowing remote software updates and electronic hardware adjustments when necessary. With a network connection Supervisors can monitor the system operation in virtual real-time to ensure normal system operation is maintained.



## The 2000 series consists of:

- Detector assemblies (1-5 panels)
- Power supply control unit
- Windows based PC
- Smart Infrared presence sensors
- Large touch screen monitor
- Remote communications package (optional)



## Controller features

- Large touch screen LCD monitor
- Windows™ based PC with high speed processing unit for menu and data management
- Large storage capacity for system operational information and alarms
- Easy to follow multilingual menu outlines and descriptions
- Multi-level security password control
- Detailed alarm data storage
- Easy to set alarm configuration menu
- Radiation levels displayed in counts per second (mR/h, nSv/h)
- Vehicle speed measurement in Km/h and mph
- Adjustable audio alarm
- Counter for number of scans in a 24 hour period and to-date
- Detailed alarm information displayed and stored after every alarm
- Network access for remote service and monitoring (optional)

## Detector features

- Large premium grade PVT scintillators
- 34.5 to 69 liters PVT volumes available (single panel)
- Low density shield on face of detector panel
- Dual layer thermal insulation protection (-20° to +50°C)
- High signal to noise ratio PMT
- High speed micro-controller with programmable CPLD technology for signal/alarm analysis
- Single input high speed pulse processor
- Noise reduction hardware/software
- Background characterization for variable ambient background suppression
- Smart infrared vehicle presence with speed monitoring
- 8 output drivers (24Vdc@50mA) for remote indicators
- Internal non-radioactive test source for detailed and repeatable system checks
- 24Vdc input voltage @1.5A

**Energy range:** 50KeV to 3.0MeV (incident)

Model #	RC2069	RC2110	RC2138
System Size (in <sup>3</sup> )	4,216	5,264	8,432
System Size (L)	69	91	138
System size is based on 2 panels. Systems may be expanded with additional panels			
PER/Panel Size (in <sup>3</sup> )	2,108	2,632	4,216
PER/Panel Size (L)	34.5	45.5	69
# of PMT's/panel	1	1	1
*Detection Capability/Overall Sensitivity-unshielded source (Shielded Source)	2.3uCi (82mCi)	2.0uCi (71mCi)	1.6uCi (58mCi)

\* Radiation measurement of <sup>137</sup>Cs (point source) at 1 meter from the face of the detector (the radiation exposure level is comparable to a 75mmø x 150mm <sup>137</sup>Cs lead sealed source buried in 40lbs/ft<sup>3</sup> (0.64 g/cm<sup>3</sup>) of scrap metal)

### Corporate Head Office

Scott Aikin  
 Saikin@radcommsystems.com  
 Jeff Adams  
 jadams@radcommsystems.com  
 2931 Portland Drive  
 Oakville, ON Canada L6H 5S4  
 Tel. +1 (905) 829-8290  
 Toll Free: 1 (800) 588-5229  
 Fax: +1 (905) 829-1406

### USA

Joshua Hunter  
 jhunter@radcommsystems.com  
 602 E. Lincolnway Ave.  
 Valparaiso, IN USA 46383  
 Tel. +1 (773) 680-8430  
 Toll Free: 1 (800) 588-5229  
 Fax: +1 (219) 510-5764

### Europe

Wim van Hove  
 wim.van.hove@radcommeurope.com  
 Watertorenweg 32, 2230 Herselt, Belgium  
 Tel. +32.14.75.02.13 Fax: +32.14.75.02.16

### China

Zhenhau Wang  
 wang.zhenhau@ehc-global.com  
 212-215 Malu Industrial Park, No. 58  
 Chen Bao Rd., Jiading  
 Shanghai, 201801, China  
 Tel. +86-21-69153031  
 Fax: +86-21-69153231

### Mexican Office

Eduardo Ballesteros  
 analiticacontrol@prodgjny.net.mx  
 Amatista No.27, El Pedregal  
 Atizapan de Zaragoza, 52948, Estado De Mexico  
 Tel: (52) 55 5077 4633/(52) 55 3615 4910

### Black Sea

Osman Tureyyen  
 metkim@metkim.com  
 Kavacik, Onarimli Sokak  
 No 9 Altay Han  
 Daire: 8 Beykoz, Istanbul, Turkey  
 Tel. +90 (216) 425-1412  
 Fax: +90 (216) 425-1432

