

Prevent costly radioactive contamination of your scrap yard, steel plant, equipment, product and personnel with the RC2000 Series vehicle radiation detection system

- Innovative design with multiple detector sizes
- User-friendly, easy to install and operate
- Detailed data storage
- Adjustable alarm threshold settings
- Network capability with email
- Ability to retrofit or upgrade existing systems



RC2000

VEHICLE RADIATION DETECTION SYSTEMS

Detection of Radioactivity in Moderate Density Materials

The RC2000 Series of radiation detection systems have been designed for moderate density materials such as compressed waste and processed scrap metal. The vehicle size and type will help determine the appropriate detector panel size (69L, 91L, 138L) and configuration. The RC2000 detection systems utilize RadComm's high quality specially prepared Polyvinyl Toluene (PVT) scintillators, electronics and Photomultiplier Tube (PMT).

Simplified System Operation

The RC2000 provides a high level of detection capability for buried Gamma Ray sources in low to moderate material densities. System operation is completely automated providing specific alarm thresholds in real-time during each scanning period. The RC2000 Series utilize a user-friendly graphical interface allowing the operator to easily move through the wide range of user options. Detailed alarms records are stored on the internal hard drive and can be easily retrieved.


Networkable Remote System Access

The RC2000 Controller is equipped with a network adaptor allowing remote monitoring, data retrieval and maintenance functions. The internal RC2000 software and hardware designs are extremely flexible allowing remote software updates and electronic hardware adjustments when necessary. With a network connection, supervisors can monitor the system operation in virtual real-time to ensure normal system operation is maintained.



The RC2000 Series consists of:

- Detector assemblies (1-5 panels)
- RadLink embedded controller
- Smart infrared presence sensors
- Large touchscreen monitor
- Remote communications package (optional)



RadLink Controller Features

- Large touchscreen LCD monitor
- Large storage capacity for system operational information and alarms
- Easy to follow multilingual menu outlines and descriptions
- Multi-level security password control
- Detailed alarm data storage
- Easy to set alarm configuration menu
- Radiation levels displayed in counts per second, as well as (mR/h, nSv/h)
- Vehicle speed measurement in km/h and mph
- Adjustable audio alarm
- Various string outputs
- Network access for remote service and monitoring
- Configurable email reporting

Detector Features

- Large premium grade PVT scintillators
- 34.5 to 69 liters PVT volumes available (single panel)
- Low density shield on face of detector panel
- Dual layer thermal insulation protection (-20°C / -4°F to 55°C/131°F)
- High signal to noise ratio PMT
- High speed micro-controller
- Single input high speed pulse processor
- Noise reduction hardware/software
- Background characterization for variable ambient background suppression
- Smart infrared vehicle presence with speed monitoring
- 8 output drivers (24Vdc@50mA) for remote indicators
- Internal non-radioactive test source for detailed and repeatable system checks
- 24Vdc input voltage @1.5A

Options

- Camera
- External alarms
- Supervisory software

Response/Sensitivity

- Energy range: 20KeV to 3.0MeV (incident)

Model #	RC2069	RC2110	RC2138
System Size (in ³)	4,216	5,264	8,432
System Size (L)	69	91	138
System size is based on 2 panels. Systems may be expanded with additional panels.			
PER/Panel Size (in ³)	2,108	2,632	4,216
PER/Panel Size (L)	34.5	45.5	69
# of PMTs/panel	1	1	1
Detection Capability/Overall Sensitivity - Unshielded Source (Shielded Source)	2.3uCi (82mCi)	2.0uCi (71mCi)	1.6uCi (58mCi)
* Radiation measurement of ¹³⁷ Cs (point source) at 1 meter from the face of the detector (the radiation exposure level is comparable to a 75mm x 150mm ¹³⁷ Cs lead sealed source buried in 40lbs/ft ³ (0.64 g/cm ³) of scrap metal)			



Corporate Head Office

Scott Aikin
Saikin@radcommsystems.com
Jeff Adams
jadams@radcommsystems.com
2931 Portland Drive
Oakville, ON Canada L6H 5S4
Tel. +1 (905) 829-8290
Toll Free. 1 (800) 588-5229
Fax. +1 (905) 829-1406

USA

Joshua Hunter
jhunter@radcommsystems.com
602 E. Lincolnway Ave.
Valparaiso, IN USA 46383
Tel. +1 (773) 680-8430
Toll Free. 1 (800) 588-5229
Fax. +1 (219) 510-5764

Europe

Wim van Hove
wim.van.hove@radcommeurope.com
Watertorenweg 32, 2230 Herselt, Belgium
Tel. +32.14.75.02.13
Fax. +32.14.75.02.16

Black Sea

Osman Tureyyen
metkim@metkim.com
Kavak, Onarimli Sokak
No 9 Altay Han
Daire: 8 Beykoz, Istanbul, Turkey
Tel. +90 (216) 425-1412
Fax. +90 (216) 425-1432

Latin America

Eduardo Ballesteros
analiticacontrol@prodginy.net.mx
Amatista No.27, El Pedregal
Atizapan de Zaragoza, 52948, Estado De Mexico
Tel. (52) 55 5077 4633/ (52) 55 3615 4910

India

Neelakshi Bhargava
neelakshi@radcommsystems.co.in
C-34, Ground Floor, Sawan Park, Ashok Vihar
New Delhi 110052, India
Tel. +91-9717671924
Fax. +91-9818650118