

**Pinpoint a potential radioactive source quickly and safely with an RC22 or RC23 Wand.**

- Fully automatic and easy to use
- Lightweight
- Extendible for longer reach
- Easy to read backlit display
- Quick response time with variable alarm tone



# RC22 & 23 WAND

TELESCOPIC RADIATION DETECTOR

## Fully Automatic and Operator Friendly

The RC22 and RC23 were designed to allow fast and easy inspection of areas, containers or vehicles that may contain radioactive material. Upon start-up the unit will perform a background check and automatically set an alarm threshold for the user. In only seconds the RC22 and RC23 is ready for use.

## Easy to Read Display with Audible Alarm

When radiation is detected the display will immediately show the increasing radiation levels. An audio alarm will also be activated to help locate the exact source of the radiation. The tone varies based upon the proximity and intensity of the radioactive source.

## Available In Two Lengths and Two Head Sizes

The RC22 is telescopic for a reach of 49" (124.5cm) to 99" (251.5cm). The telescopic pole serves two functions. One is to reach and scan an area that would normally be out of reach, and the second is to provide a safer operating distance between you and a potential radioactive source.

The wand is available in two different detector head sizes. The RC22 has a detector head size of 2" (5.1cm) for a total volume of 193cc. For greater sensitivity, the RC23 has a detector head size of 3" (7.6cm) for a total volume of 442cc.



## RC22 & RC23 Specifications

### Display

- Backlit RGB colour LCD 320x240 resolution
- Viewing area: 3.5"(8.9cm) TFT LCD
- Display radiation level in selected unit of measurement, battery life, background level, and alarm threshold

### Operation

- Single button activation automatically sets audio alarm threshold level and displays unit of measurements (CPS, nSv/h, uR/h)

### Energy Response Range

- From 30Kev – 3.0Mev

### Temperature Range

- -20°C to +60°C (-4°F to +140°F)

### Battery

- 2 sets of NiMH 10,000 mA/h rechargeable or 2 sets of "D" cell batteries

### Size

Model	Head Size	Extendible Length	Weight	Detector Size
RC22 Standard	2" (5.1 cm)	49" (124.5 cm) to 68" (172.7 cm)	5.2 lbs (2.36 kg)	193 cc
RC22 Long	2" (5.1 cm)	68" (172.7 cm) to 99" (251.5 cm)	5.4 lbs (2.72 kg)	193 cc
RC23	3" (7.6 cm)	49" (124.5 cm) to 68" (172.7 cm)	6.0 lbs (2.45 kg)	442 cc

## Each RC22 and RC23 Package Includes:

- RC22 or RC23 fully charged and ready for use
- Carrying case
- Rubber tip boot cover (Quantity 2)
- Universal battery charger
- Operation manual



### Corporate Head Office

Scott Aikin  
Saikin@radcommsystems.com  
Jeff Adams  
jadams@radcommsystems.com  
2931 Portland Drive  
Oakville, ON Canada L6H 5S4  
Tel. +1 (905) 829-8290  
Toll Free. 1 (800) 588-5229  
Fax. +1 (905) 829-1406

### USA

Joshua Hunter  
jhunter@radcommsystems.com  
602 E. Lincolnway Ave.  
Valparaiso, IN USA 46383  
Tel. +1 (773) 680-8430  
Toll Free. 1 (800) 588-5229  
Fax. +1 (219) 510-5764

### Europe

Wim van Hove  
wim.van.hove@radcommeurope.com  
Watertorenweg 32, 2230 Herselt, Belgium  
Tel. +32.14.75.02.13  
Fax. +32.14.75.02.16

### Black Sea

Osman Tureyyen  
metkim@metkim.com  
Kavaik, Onarimli Sokak  
No 9 Altay Han  
Daire: 8 Beykoz, Istanbul, Turkey  
Tel. +90 (216) 425-1412  
Fax. +90 (216) 425-1432

### Latin America

Eduardo Ballesteros  
analiticacontrol@prodginy.net.mx  
Amatista No.27, El Pedregal  
Atizapan de Zaragoza, 52948, Estado De Mexico  
Tel. (52) 55 5077 4633/ (52) 55 3615 4910

### India

Neelakshi Bhargava  
neelakshi@radcommsystems.co.in  
C-34, Ground Floor, Sawan Park, Ashok Vihar  
New Delhi 110052, India  
Tel. +91-9717671924  
Fax. +91-9818650118