

## Prevent costly radioactive contamination of your scrap yard, steel plant, equipment, product and personnel with the RC4000 Series vehicle radiation detection system

- Innovative design with multiple detector sizes
- Energy specific alarm and background statistical analyses
- Real-time density tracking algorithm
- Remote calibration software. No source needed
- Network capability with email
- User-friendly, easy to install and operate
- Ability to retrofit or upgrade existing systems
- Compliant ANSI N42.35-2016 Gamma Radiation Response

# RC4000

## VEHICLE RADIATION DETECTION SYSTEMS

### Detection of Radioactivity in High Density Materials


The RC4000 Series of radiation detection systems have been designed to detect very low Gamma Ray emissions in high density materials. The vehicle size and type will help determine the appropriate panel size and configuration. The RC4000 is supplied in a variety of detector panel sizes with any configuration for up to 8 detector panels. The RC4000 detection systems utilize RadComm's high quality Polyvinyl Toluene (PVT) scintillators, electronics and Photomultiplier Tubes (PMT).

### Simplified System Operation

The RC4000 utilizes real-time statistical algorithms that are based on Gamma Energy Distribution to ensure alarm thresholds levels are optimized. The RC4000 utilize a user-friendly graphical interface allowing the operator to easily move through the wide range of user options. All detailed Clean Scan, Testing and Alarms records are stored on the internal hard drive and can be easily retrieved and interpreted as required.

### Remote System Access

The RC4000 Controller is equipped with a network adaptor allowing remote monitoring, data retrieval and maintenance functions. The internal software and hardware designs are extremely flexible allowing remote software updates and electronic hardware adjustments when necessary. Supervisors can monitor the system operation in real-time to ensure normal system operation is maintained. Also, with a network connection the system has the capability of emailing alarms and system malfunctions.



## The RC4000 Series consists of:

- Detector assemblies (1-8 panels)
- RadLink embedded controller
- Smart Infrared presence sensors
- Large touchscreen monitor
- Remote communications package (optional)



## RadLink Controller Features

- Touchscreen LCD monitor
- Large storage capacity for system operational information and alarms
- Easy to follow multilingual menu outlines and descriptions
- Multi-level security password control
- Detailed alarm data storage
- Manual scanning for pinpointing source location within the vehicle's load
- Easy to set alarm configuration menu
- Network access for remote service and monitoring
- Radiation levels displayed (mR/h, nSv/h, cps)
- Vehicle speed measurement in km/h and mph
- Ambient temperature displayed in Celsius and Fahrenheit
- Adjustable audio alarm
- Counter for number of scans in a 24-hour period and to-date incoming and outgoing
- Detailed alarm information displayed and stored after every alarm

## Detector Features

- Large premium grade PVT scintillators
- 34.3 to 69 liters PVT volumes available (single panel)
- Low density shield on face of detector panel
- Dual layer thermal insulation protection (-20°C/-4°F to 55°C/131°F)
- High signal to noise ratio PMTs (up to 2)
- High speed micro-controller
- Dual input high speed pulse processor
- Noise reduction hardware/software
- Background characterization for variable ambient background suppression
- Smart infrared vehicle presence with speed monitoring
- 8 output drivers (24Vdc@50mA) for remote indicators
- Internal non-radioactive test source for detailed and repeatable system checks
- 24Vdc input voltage @1.5A
- System auto-stabilization & remote calibration
- Suitable for Vehicle, Rail, Charge Bucket, Off Gas and Conveyor Systems

## Options

- Camera
- External alarms
- Supervisory software
- Neutron Detection

## Response/Sensitivity

- Energy range: 20KeV to 3.0MeV (incident)

Model #	RC4069	RC4110	RC4138
System Size (in <sup>3</sup> )	4,216	5,376	8,432
System Size (L)	69	88	138
System size is based on 2 panels. Systems may be expanded with additional panels.			
PER/Panel Size (in <sup>3</sup> )	2,108	2,688	4,216
PER/Panel Size (L)	34.5	44	69
# of PMTs/panel	1	2	2
Detection Capability/Overall Sensitivity - Unshielded Source (Shielded Source)	1.6μCi (58mCi)	1.4μCi (50mCi)	1.1μCi (41 mCi)
* Radiation measurement of <sup>137</sup> Cs (point source) at 1 meter from the face of the detector (the radiation exposure level is comparable to a 75mm x 150mm <sup>137</sup> Cs lead sealed source buried in 40lbs/ft <sup>3</sup> (0.64 g/cm <sup>3</sup> ) of scrap metal)			



**Corporate Head Office**  
 Scott Aikin  
 Saikin@radcommsystems.com  
 Jeff Adams  
 jadams@radcommsystems.com  
 2931 Portland Drive  
 Oakville, ON Canada L6H 5S4  
 Tel. +1 (905) 829-8290  
 Toll Free. 1 (800) 588-5229  
 Fax. +1 (905) 829-1406

**USA**  
 Joshua Hunter  
 jhunter@radcommsystems.com  
 602 E. Lincolnway Ave.  
 Valparaiso, IN USA 46383  
 Tel. +1 (773) 680-8430  
 Toll Free. 1 (800) 588-5229  
 Fax. +1 (219) 510-5764



**Europe**  
 Wim van Hove  
 wim.van.hove@radcommeurope.com  
 Watertorenweg 32, 2230 Herselt, Belgium  
 Tel. +32.14.75.02.13  
 Fax. +32.14.75.02.16

**India**  
 Neelakshi Bhargava  
 neelakshi@radcommsystems.co.in  
 C-34, Ground Floor, Sawan Park, Ashok Vihar  
 New Delhi 110052, India  
 Tel. +91-9717671924  
 Fax. +91-9818650118